



assignable as PGM, PVW, AUX, multi-screen
and keyout.

Reference

Loop through x 1 (Genlock)
Black burst x 1 (internal synchronization)

WIPE/DVE

Pattern

WIPE x 12, Squeeze x 11, SLIDE x 8, 3D DVE x
12 (3 directions)

background.

Excluding 3D, selection with key transition is possible independently of

Transition

Transition method

FADER, AUTO

Transition type

Cut, mix, wipe (including DVE), background and
key can be selected.

KEYER

Key source

BUS

Key fill

BUS, MATTE

Key mode

Linear key, Lum key, Chroma key (Key only)

PinP

Transition method

AUTO (PinP only)

Transition type

MIX

Interface

Serial (EDITOR)

Dsub9pin x 1: RS422A (GVG protocol compatible)

Tally output

Dsub15pin x 1, open collector output

GPI

3.5 Stereo mini jack

Ethernet

100 Mbps/10 Mbps x 1 (Service purpose)

Removable media

SD memory card slot

1 (for transferring still image files and providing
an upgrade capability)

Power

Power Source

AC 220 V to 240 V, 50 Hz/60 Hz

Dimensions(W x H x D)

420 mm x 132 mm x 408 mm (excluding protrusions)
possible independently of background.