



Panasonic PT-D6000E Projector



Specification		
System		DLP™ Projection system
Device		0.7" diagonal (4:3 aspect ratio) DLP™ chip x 1
Pixels		786,432 (1,024 x 768) x 1, total of 786,432 pixels
Lamp		300 W UHM lamps (x 2) (Dual Lamp System)
Brightness		6,500 lumens (dual lamp, high power mode)
Contrast ratio		2,000:1 (full on/full off, contrast mode: high)
Resolution		1,024 x 768 pixels
Lens	PT-D6000S	Powered zoom/focus lenses (1.8 - 2.4:1), F = 1.7 - 2.0, f 25.6 - 33.8 mm
	PT-D6000LS	Optional powered zoom/focus lenses
Screen size		50 - 600 inches (50 - 200 inches with the ET-DLE055), 4:3 aspect ratio
Optical axis shif		Vertical: +50% (powered), horizontal: ±10% (powered)
Scanning frequency	DVI-D	Horizontal: 15-91 kHz, Vertical: 50-85 Hz Dot clock: 162 MHz or lower
	RGB	Horizontal: 15-91 kHz, Vertical: 50-85 Hz Dot clock: 162 MHz or lower
	YPBPR (YCBCR)	525i (480i), 625i (576i), 525p (480p), 625p (576p), 750 (720)/60p, 750 (720)/50p, 1035/60i, 1125 (1080)/60i, 1125 (1080)/50i, 1080/24p,
	S-Video/Video	Horizontal: 15.75/15.63 kHz, Vertical: 50/60 Hz (NTSC, NTSC4.43, PAL, PAL60, PAL-N, PAL-M, SECAM)
Terminals	DVI-D IN	DVI-D 24-pin
	RGB 1/ YPBPR IN	BNC x 5
	RGB2 IN/ YPBPRIN	D-sub HD 15-pin
	VIDEO IN	BNC
	S-Video IN	Mini DIN 4-pin
	SERIAL IN	D-sub 9-pin (RS-232C compliant)
	SERIAL OUT	D-sub 9-pin
	REMOTE 1 IN	M3 jack
	REMOTE 1 OUT	D-sub 9-pin
LAN	RJ-45 for network connection, 10Base-T/100Base-TX, compliant with PLink™	
Keystone correction range		Vertical: ±40° (±30° with the ET-DLE055)
Installation		Ceiling/floor, front/rear
Power cord length		3.0m (9'10")
Power supply	PT-D6000US (North America)	120V AC, 50/60 Hz
	PT-D6000ES (Europe, Asia)	220 - 240V AC, 50/60 Hz
Power consumption	PT-D6000US (North America)	780 W (780 VA) or less, Eco standby mode: 0.2W Standby mode normal: 8 W (Both with fan stopped)*3
	PT-D6000ES (Europe, Asia)	750 W (840 VA) or less, Eco standby mode: 0.3W Standby mode normal: 9 W (Both with fan stopped)*3
Dimensions (W x H x D)		498 mm x 175 mm x 440 mm (19-19/32" x 6-7/8" x 17-5/16") (with supplied lens)
		498 mm x 175 mm x 432 mm (19-19/32" x 6-7/8" x 17") (without lens)
Weight		Approx. 16.0 kg (35.3 lbs) (with supplied lens)
		Approx. 15.2 kg (33.5 lbs)(without lens)
Operating temperature		0 - 45 °C (32% - 113 °F)
Operating humidity		20 - 80% (no condensation)
Supplied accessories		Power cord, Wireless/wired remote control unit, Batteries for remote control (AA type for North/South America, R6/LR6 type for Europe / Asia) x 2, Wire rope